

BreadCrumb® ME 2

Portable Wireless Mesh Network Node

APPLICATIONS

► MINING

For open pit and underground mines, BreadCrumb® devices form a resilient network for mine monitoring and control. Typical applications include Miner Tracking, Emergency Rescue, Voice communications (VoIP), Dispatch, Routing, Health Monitoring and Video.

► MILITARY


With battery power, rugged enclosures, single-switch operation and robust security, BreadCrumb® devices are perfect for military applications such as Perimeter Security, Sensor Data Collection, Video Surveillance, Convoy Security, RFID Tracking & more. Depending on BreadCrumb® model, security options range from WEP, WPA2, SecNet 11® to FIPS 140-2.

► FIRST RESPONDERS

BreadCrumb® devices form an instant secure network for emergency response, disaster relief, RFID tagging, voice communications (VoIP), PDAs, laptops, video and sensor applications. The included Ethernet port can provide Internet access through satellite or microwave links.

InstaMesh®

Rajant has developed this state-of-the-art Linux based software over the last 6 years for mission critical applications. InstaMesh® resides on each BreadCrumb®, allowing for hundreds of resilient mesh connections to other BreadCrumb® devices, even while they are moving.



In the above diagram, the Rajant mesh network quickly adapts to the changes caused by the movement of Node E. New resilient links are established in real-time keeping the network available, intact and secure.

Rajant BreadCrumb® ME2

The Rajant BreadCrumb® ME2 is a rugged wireless transmitter-receiver that forms a mesh network (using InstaMesh®) when used in conjunction with other BreadCrumb® devices. This portable wireless mesh network node supports an open-standard IEEE 802.11 b/g radio with up to two antennas to enable data, voice and video applications. This ME2 device also supports FIPS 140-2* and requires only a single switch to operate.



BreadCrumb® ME2 Benefits

- *FIPS 140-2 security encryption (pending certification) to ensure privacy of data
- Self-healing for resilient connections & high availability
- Rugged & portable for applications in extreme situations
- Open system IEEE 802.11 standards for compatibility with millions of commercial off-the-shelf (COTS) client devices such as laptops, PDAs, IP cameras, sensors, VoIP phones & other IP devices
- Runs InstaMesh® so that the network quickly adapts to moving network elements
- Battery-powered for mobile applications
- High bandwidth availability for data, voice & video applications
- Single switch & self-configuring operation for fast & easy deployments

BC Admin® Management Tool

The included BC Admin® tool is used to configure, manage and monitor your Rajant network.




- Topology map shows BreadCrumb® and client device connections
- BreadCrumb®/client device channel, frequency, MAC address, IP address, nickname assignment, signal and noise levels
- BreadCrumb® 'time since last update' & battery levels
- Channel and link speed of connections
- Manual radio, SSID, DHCP, reach-back, gateway & port forwarding settings
- Access control, security, and encryption settings
- Remote zeroization of encryption & more

Rajant BreadCrumb® ME2



BreadCrumb® ME2



WIRELESS

Radios	(1) IEEE 802.11 b/g
Integrated Antenna (s)	NA (External only)
External Antenna Connector (s)	(2) SMA (f)
Frequency	2.402–2.472 GHz/U.S. (Varies with country)
Modulation	DSSS: DBPSK @ 1 Mbps , DQPSK @ 2 Mbps, CCK @ 5.5 and 11 Mbps
RF Output Power	26 dBm ± 1 dB
Receive Sensitivity	1 Mbps: -97 dBm +/- 2 dB 54 Mbps: -74 dBm +/- 2 dB
Range	11.2 km (7 mi) (Range can vary due to antenna type, non-line-of-sight, obstruction and RF noise factors)

NETWORK AND SECURITY

Ethernet	(1) IEEE 802.2, RJ-45 10/100 Mbps
Managed Network Features	Access Point, Bridge, Gateway, DHCP, NAT & Port Forwarding
Security	FIPS 140-2 (pending cert.), AES-256 on Backbone; Access Control Lists; WEP; WPA; WPA2; Compatible with Layer-2 and Layer-3 client/server & peer-to-peer security solutions

POWER

Input Voltage	6–15 VDC
Power Consumption	4.8 Watts @ 12VDC (19.2 Watts @ 12VDC with full UDP transfers)
Optional Battery	9V / 900 mAh internal battery; 9V / 5400 mAh external battery

PHYSICAL

Dimensions	17.8cm x 12.1cm x 4.3cm (7" x 4.75" x 1.7")
Weight	0.36 kg (0.8 lbs)
Temperature	Storage: -40°C to 80°C (-40°F to 176°F) Operating: -20°C to 60°C (-4°F to 104°F)
Humidity	95% (non-condensing)
Certification	FCC Class B, Industry Canada
Warranty	1 Year

► www.rajant.com



Rajant Corporation • 400 East King Street • Malvern, PA • 19355 • tel 484.595.0233 • fax 484.595.0244

© 2007 Rajant Corporation. All rights reserved. Specifications subject to change without notice. BreadCrumb and InstaMesh are registered trademarks of Rajant Corporation. 04/2008